


ET-2 port tap range



- High quality 2-way installation taps
- Modem Safe™ surge protection and intermodulation reduction solution
- High return loss
- CPD Safe™ - NiSn plated housing, silver plated beryllium copper F-contacts
- Easy to install - compact and stackable in-line model
- 7 mm stand-off space to fit cable underneath
- Grounding block option available
- Exceeds EN Class A screening requirements



Overview

Products within the Ecoline range excel both in electrical and mechanical performance. Though designed for use within indoor environments, they are also specified for use within street-side plant.

Ecoline products are designed for easy installation, have a compact housing and some models are stackable. All F-connectors used on Ecoline products meet the SCTE standards (ANSI SCTE 02 2006). The F-inner spring is designed to connect coax cables with an inner core of 0.56 to 1.30 mm. It retains this elasticity and provides effective clamping force even when varying thicknesses of inner conductor are connected in succession.

The intermodulation performance, which is an important factor in high level return path signals, has been greatly improved through a newly developed ferrite and specially designed circuits.

The high frequency shielding exceeds Class A requirements (EN-50083-2:2006) over the whole frequency range from 5 MHz to 1000 MHz.

Modem Safe

Modem Safe is a highly effective surge protection solution for sensitive network and in-home CPE. Based on passive circuits, the technology does not rely on discharge tubes, extending the lifespan of the solution.

- Blocks high and low voltage pulses and unwanted DC voltages
- Prevents internal ferrites within the product from becoming magnetised (avoiding deterioration in the performance of CPE)
- Drives fewer reported faults
- Improves customer service
- Reduces truck rolls

CPD Safe

CPD (Common Path Distortion) is well known for producing signal interference on networks. It is caused by electrolytic corrosion or the oxidation of dissimilar metals when in close contact. CPD Safe technology protects against CPD.

- Removes a primary cause of CPD
- Reduces signal interference on the network
- Drives fewer reported faults
- Reduces truck rolls
- Improves customer service

Specifications

		MHz	8dB		12dB		16dB		20dB		24dB	
			Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max
Insertion loss (dB)	In to Out	5-65	4.2	4.6	1.2	1.6	1.2	1.6	0.8	1.2	0.9	1.3
		65-300	4.0	4.4	1.2	1.6	1.1	1.5	0.7	1.1	0.7	1.1
		300-550	3.7	4.1	1.3	1.7	1.3	1.7	0.8	1.2	0.8	1.2
		550-750	3.6	4.0	1.4	1.8	1.4	1.8	0.9	1.3	0.8	1.2
		750-862	3.8	4.2	1.6	2.0	1.4	1.8	1.1	1.5	1.0	1.4
		862-1006	3.8	4.2	1.6	2.0	1.5	1.9	1.1	1.5	1.0	1.4
	In to Tap	5-65	8.4	10.0	12.5	14.0	15.6	18.0	19.8	22.0	24.2	26.0
		65-550	8.1	9.5	12.4	13.5	15.7	17.5	19.4	21.5	24.0	25.5
550-1006		8.1	9.5	12.6	13.5	15.9	17.5	19.5	21.5	24.0	25.5	
Return loss (dB, typ)	All ports	5-15	29.0		26.0		25.8		28.8		26.3	
		15-550	26.5		24.2		25.8		27.4		24.3	
		550-1006	23.8		24.6		25.5		28.0		25.1	
Isolation (dB)	Tap to Tap		Typ	Min	Typ	Min	Typ	Min	Typ	Min	Typ	Min
		5-65	41.8	40.0	54.5	40.0	59.6	40.0	63.4	40.0	69.3	40.0
		65-550	39.6	36.0	51.3	36.0	49.4	36.0	52.8	36.0	53.4	36.0
Directivity	Out to Tap	5-65	37.4	32.0	42.1	32.0	42.6	36.0	43.6	40.0	48.2	44.0
		65-550	36.4	32.0	37.4	32.0	44.8	36.0	45.3	40.0	46.7	44.0
		550-1006	33.4	27.0	31.4	27.0	35.2	31.0	41.7	33.0	44.0	35.0
Screening efficiency (dB) ¹		5-300	>95									
		300-470	>90									
		470-950	>85									
		950-1000	>85									
Shielding effectiveness (dBi) ²		5-300	Avg 130									
		300-1000	Avg 120									
Intermodulation p+q (dBc, min) ³		-115.0										
Surge Class conformance ⁴	All ports	1 kV 1.2/50µs										
Connectors	All ports	F-female										
Material	Housing	NiSn plated zinc die-cast										
	F-spring	Silver plated beryllium copper										
Impedance (Ohm, typ)		75										
Dimensions (mm)	L x H x D	80.3 x 49.8 x 24.4										
Equipment Approval	CE											

Remarks

- 1 Tested according to EN 50083-2 2006
- 2 Tested according to SCTE IPS-TP403
- 3 Two carriers (50 & 55MHz), out to in, @ 120dBµV, after 10 pulses (25V/1,2µS rise time/500µS duration) at all ports
Two carriers (50 & 55MHz), out to in, @ 120dBµV, after 1 pulse 1KV (1,2µS risetime/50µS fall time) at Input.
- 4 Tested according to IEC 61000-4-5 2005
DC power blocking all ports

Ordering information

(without grounding block)

(with grounding block)

Item Name	Article number	Item Name	Article number
ET-2-8+/N	10430081	ET-2-8+/N-G	10430442
ET-2-10+/N	10430085	ET-2-10+/N-G	10430443
ET-2-12+/N	10430082	ET-2-12+/N-G	10430444
ET-2-14+/N	10430034	ET-2-14+/N-G	TBA
ET-2-16+/N	10430083	ET-2-16+/N-G	10430445
ET-2-20+/N	10430084	ET-2-20+/N-G	10430446
ET-2-24+/N	10430086	ET-2-24+/N-G	10430447

Measurements taken at room temperature

© Copyright 2011 Technetix Group Limited. All rights reserved.

This document is for information only. Features and specifications are subject to change without notice. Technetix, the Technetix logo, Ingress Safe, Modem Safe and certain other marks and logos are trade marks or registered trade marks of Technetix Group Limited in the UK and certain other countries. Other brand and company names are trade marks of their respective owners. Technetix protects its technology and designs by registering patents, trade marks and designs in Europe and certain other countries.