

- IEC-male, IEC-female, Push-on F-male
- Shielding in excess of Class A+
- Fast reliable coax cable termination
- Long service life
- Enables installer to see the coaxial core while installing
- Easy installation
- Kabel Keur / Ziggo certified



IEC-female



IEC-male



Push-on  
F-male

## Overview

Technetix-Pro Right Angle connectors are a quick easy alternative to traditional coax cable connector terminations that provide reliable termination that last, ensuring reliability that minimises the need for unwarranted truck rolls to connector issues.

Technetix-Pro Right Angle connectors have assured shielding across the required frequency range that exceeds Class A+ requirements.

Technetix-Pro Right Angle connectors are robust, being made of Zamak plated with zinc that is then subjected to a dichromate and reactive sealing process.

## Specifications

### Standards

Standard	Title	Part
Forward Path	Forward Path	85/258-1218
Forward Path	Return Path	5-65/204

### Technical data

Port	Tip	Range	Direction	Connector
1	Chassis			Enclosure
2	Radio frequency	5 MHz - 1218 MHz	Bidirectional	Flanges
3	Radio frequency	5 MHz - 1218 MHz	Bidirectional	CEI

### Shielding

Band	Frequency (MHz)	Level (dB)	Class A Limit	Class B Limit
-	30.10	101.88	85.00	75.00
TV Band I (Channels 2 -4)	50.10	105.99	85.00	75.00
FM Radio Band II	100.00	104.54	85.00	75.00
TV Band III (Channels 5 - 12)	200.00	96.03	85.00	75.00
High S Band	300.00	95.76	85.00	75.00
Hyperband	400.01	94.13	80.00	70.00
TV Band IV (Channels 21 - 69)	470.00	93.94	80.00	70.00
TV Band IV (Channels 21 - 69)	500.01	97.91	75.00	65.00
TV Band IV (Channels 21 - 69)	600.01	96.13	75.00	65.00
TV Band V (Channels 37 - 69)	700.00	92.14	75.00	65.00
TV Band V (Channels 37 - 69)	800.00	90.80	75.00	65.00
-	900.00	88.71	75.00	65.00
-	950.00	87.21	55.00	50.00
-	1000.00	87.40	55.00	50.00
-	1100.00	87.99	55.00	50.00
-	1200.00	86.11	55.00	50.00
-	1300.00	85.77	55.00	50.00

### Data

Frequency range	Insertion loss	Return loss
0 - 500 MHz	-0.1 dB	-25 dB
500 - 1000 MHz	-0.14 dB	-19 dB
1000 - 1218 MHz	-0.2 dB	-15 dB