

TWO-265/D-1G semi-isolated wall outlet



- **Dual output isolators - TV and Data**
- **5 - 1006 MHz**
- **Optimised for a 85 / 105MHz bandwidth split**
- **Modem Safe™ surge protection and intermodulation reduction solution**
- **Meets EN Class A screening requirements**
- **High isolation between ports**
- **Diplexers for low upstream attenuation**
- **Easy to install**
- **Loop and non-loop through versions available**



Overview

Designed for easy in-home installation, the TWO series contains wall outlets to suit a range of home network configurations.

The TWO-265/D-1G is used to connect a cable modem and a TV set to the cable network. High isolation between output ports is achieved by using high quality diplex filters and prevents the cable modem from generating interference on the TV channels.

Low upstream attenuation on the cable port provides cable operators with greater flexibility in the return path.

The TWO-265/D-1G's durable zinc die-cast housing with high quality in and output connectors offers trouble-free multimedia connectivity.

The different connectors for TV (IEC male) and the data port (F-female) clearly mark the dedicated connection points for TV and data applications.

The TWO-265/D4-1G has a loop through feature for cascaded in home networks.

Modem Safe

Modem Safe is a highly effective surge protection solution for sensitive network and in-home CPE. Based on passive circuits, the technology does not rely on discharge tubes, extending the lifespan of the solution.

- Blocks high and low voltage pulses and unwanted DC voltages
- Prevents internal ferrites within the product from becoming magnetised (avoiding deterioration in the performance of CPE)
- Drives fewer reported faults
- Improves customer service
- Reduces truck rolls

TWO-265/D-1G semi-isolated wall outlet

Specifications

		MHz	TWO-265/D-1G	TWO-265/D4-1G
Insertion loss (dB, max)	In -> Out	5 - 1006	N/A	4.5
	In -> Data	105 - 862	4.8	9.3
		862 - 1006	5.0	9.3
	Data -> In	5 - 85	1.3	5.3
	In -> TV	105 - 862	4.8	9.3
		862 - 1006	5.3	9.3
Return loss (dB, min)	In	5 - 85 ¹	18.0	18.0
		105 - 1006 ¹	18.0	18.0
	Data	5 - 85	20.0	18.0 ¹
		105 - 1006 ¹	18.0	18.0
	TV	105 - 1006 ¹	18.0	18.0
Isolation (dB, min)	Data -> Out		N/A	22.0 ¹
	TV -> Data	5 - 85	45.0	45.0
		105 - 862	22.0	22.0 ¹
		862 - 1006	20.0	22.0 ¹
Screening efficiency (dB, typ) Minimum exceeds Class A ²		5 - 300	85.0	85.0
		300 - 470	80.0	80.0
		470 - 1006	75.0	75.0
		950 - 1006	85.0	85.0
Connectors	In		Terminal Block	
	Data		F-female	
	TV		IEC-male	
Material	Housing		Nickel plated zinc die-cast Back cover tin plated steel sheet	
	F-spring		Silver Plated Phosphor Bronze	
Impedance (Ohm, typ)			75	
Dimensions (mm)	L x H x D		70.2x70.2x30.0	
Equipment Approval			CE	

Remarks

- Where frequency is above 40MHz, deduct 1.5dB/Octave (with a minimum of 10dB)
- Transfer Impedance method according to IEC 60728-2 (5-30MHz), Absorption Clamp method according to IEC-60728-2§4.4 (30-1000MHz)

Ordering information

Item Name	Article number
TWO-265/D-1G	19010057
TWO-265/D4-1G	19010058