## **EWAX-XX Wideband equalisers**



- Wideband equalisers 1.2 GHz ranging from 1 dB to 8 dB
- Low insertion loss
- Complies with EN50083-2 Class A++ standard
- Suitable for use in the headend, street cabinets and at customer premises
- **■** Tubular nickel plated brass housing



#### **Overview**

The Technetix EWAX series is a range of high quality, wideband equalisers, providing a range of dB variants from 1 dB to 8 dB.

These Class A++ equalisers have a frequency range running from 5 MHz to 1.2 GHz and maintain a good return loss.

The small tubular housing and connectors are made of brass and have nickel plating.

# **EWAX-XX** Wideband equalisers



## **Electrical specifications**

		1 dB	2 dB	3 dB	4 dB	5 dB	6 dB	8 dB		
	Frequency range	Тур	Unit	Notes						
Incombine Incom	5 MHz	1.0	2.0	3.0	4.0	5.0	6.0	8.0	dB	1&3
Insertion loss	1218 MHz	0.5	0.5	0.5	0.5	0.5	0.7	0.7	dB	1
Return loss	5 MHz - 1218 MHz	20	20	20	20	20	20	20	dB	2
Impedance					75				Ohm	

### **Specifications**

IP rating	IPx4				
Housing material	Nickel plated brass				
Dimensions	L x D (mm) 41 x 12.5				
Weight	Grams 17				
Connector construction	Male and female 'F' type				
	CE				
Favinment engage	Class A++				
Equipment approval	Meets EN 50083-2 standard				
	RoHS compliant				

#### Notes

Hotes					
1	± 0.5dB				
2	Always >14 dB				
3	Connectors tested in accordance with IEC66169				

#### Ordering information

Item Name	Article Number		
EWAX-01	19012652		
EWAX-02	19012653		
EWAX-03	19012654		
EWAX-04	19012655		
EWAX-05	19012656		
EWAX-06	19012657		
EWAX-08	19012658		